



FX65 | FX80 | FX105 | FX135 SOFTMOUNT WASHER-EXTRACTORS



TOUCH CONTROL AVAILABLE
Multilingual user-friendly 7" touch control



500G EXTRACTION SPEED
Less moisture for a more efficient drying process



CLOUD-BASED PLATFORM
to easily monitor your laundry everywhere and at any time



IMPROVED DURABILITY
for your peace of mind with a 3-year warranty



CASCADE DRUM TECHNOLOGY
Extra mechanical action thanks to its cascading shape of the surface

FEATURES & BENEFITS


Features	Options	Control
- Stainless steel top, drum and tub and anthracite front and side panel - Patented soap hopper - Easy access to all vital parts from the front - Large door opening for easy loading & unloading - Cascade Drum - Patented drum	- Coin operated - Stainless steel cabinet - Liquid soap connection and pumps - Water recovery kit - Steam heating version 3rd water inlet	- XControl FLEX PLUS – fully programmable and customizable cycles 7" touch screen. - User-friendly screen with operating instructions built in as part of the control - Complete control content available in 34 languages - XControl – fully programmable control with 20 Pre-set programs and memory up to 99. - XTronic – Programmable control with 6 programs (+2 cycle modifiers and Imbalance detection)

SPECIFICATIONS

TYPE		FX65	FX80	FX105	FX135
INNERDRUM					
Capacity 1:09	kg (lb)	7 (15)	8,5 (19)	12 (26)	15 (33)
Capacity 1:10	kg (lb)	6,5 (14)	7,5 (17)	10,5 (23)	13,5 (30)
Volume	litres	65	75	105	135
Diameter	mm	530	530	620	620
DRUM SPEED					
Wash	rpm	49	49	49	49
Extraction	rpm	1298	1298	1200	1151
G-FACTOR		500	500	500	460
HEATING					
Electricity	kW	3 - 7	3 - 7	3 - 7	3 - 9
Steam	bar	1 - 8	1 - 8	1 - 8	1 - 8
Hot water	°C	90	90	90	90
Sound pressure level	dB (A)	< 65	< 65	< 65	< 65
Water valves connection	BSP	3/4"	3/4"	3/4"	3/4"
Water pressure	kPa	100-600	100-600	100-600	100-600
Rec. water pressure	kPa	300-500	300-500	300-500	300-500
Water inlet	l/min	20	20	20	20
Drain valve	outer Ø mm	76	76	76	76
Flow amount with drain valve	l/min	210	210	210	210
Steam valve connection	BSP	1/2"	1/2"	1/2"	1/2"
Steam pressure	kPa	100-800	100-800	100-800	100-800
DIMENSIONS					
Size H×W×D	mm	1135×710×740	1135×710×790	1245×795×795	1245×795×945
Net weight	kg	170	185	210	255
TRANSPORT DATA					
Packed H×W×D	mm	1245×750×840	1245×750×840	1345×835×840	1345×835×985
Gross weight	kg	180	200	235	275

DIMENSIONS

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	S	T	U	V	W	X	Y
FX65	612	564	710	24	349	1135	180	48	740	676	1030	1030	940	480	88	230	203	67	1030	42	293	390	218	113
FX80	612	564	710	24	349	1135	180	48	790	726	1030	1030	940	480	88	230	203	67	1030	42	293	390	218	113
FX105	648	600	795	24	342	1245	180	48	795	726	1140	1140	1050	506	88	230	203	67	1140	42	293	475	218	113
FX135	648	600	795	24	342	1245	180	48	945	876	1140	1140	1050	506	88	230	203	67	1140	42	293	475	218	113
	width				height				depth															



- | | | |
|-------------------------------------|--|--|
| 1. Control panel | 9. Cold water inlet, soft | 17. USB port - optional |
| 2. Soap dispenser | 10. Cold water inlet, hard | 18. PC programming connection |
| 3. Central stop button | 11. Electrical connection | 19. Discharge water cable inlet |
| 4. Steam connection | 12. Hot water inlet | 20. Drain valve - 3 in. [76 mm] |
| 5. Air relieve | 13. Main switch | 21. Water Sample - 1/2 in. (Applicable for wash bath sample-on request only) |
| 6. Liquid soap connection | 14. Heating change-over switch | |
| 7. Recycle water inlet | 15. Liquid soap pump electrical connection | |
| 8. Recycled water valve cable inlet | 16. Fuses | |