



#### LEGEND:

1. Control panel
2. Door handle
3. Soap dispenser
4. Centralstop button
5. Liquid soap connection
6. Cold soft water inlet
7. Cold hard water inlet
8. Hot water inlet
9. Electrical connection
10. Main switch
11. Electrical connection to liquid soap pumps
12. Fuses
13. USB port
14. Drain outlet
15. Steam inlet

## TECHNICAL SPECIFICATION

Capacity:	1:10 – 11 kg / 25 lbs max. 1:9 – 12 kg / 26.5 lbs
Inner drum dimensions: diameter	620 mm / 24.4"
Drum volume:	105 dm <sup>3</sup> / 27.7 gal
Drum revolutions: wash high extraction	49 rpm 1075 rpm
G-faktor:	400
Machine dimensions (max.): width depth height	795 mm / 31.3" 795 mm / 31.3" 1250 mm / 49.2"
Weight: netto brutto	210 kg / 463 lbs 235 kg / 518 lbs
Machine electrical execution:	E: 3x380–415V+N 50Hz S: 1x200–240V 50Hz (A)
Rated motor power:	1.1 kW
Rated heating power input:	9 kW
Rated input power of the machine:	E: 9.8 kW S: 1.2 kW (A)
Power supply protection – with el. heating – without heating	9 kW/3AC 400V/20A 1AC 16A
Conductors section (E / S )	5x2.5 mm <sup>2</sup> Cu / 3x2.5 mm <sup>2</sup> Cu
Connections: water pressure water connection – standard / option drain connection Steam connection BSP Steam pressure	0.3 ÷ 0.5 MPa / 44 ÷ 73 psi 2x <sup>3</sup> / <sub>4</sub> " / 3x <sup>3</sup> / <sub>4</sub> " ø76 mm / 3" DN15 <sup>1</sup> / <sub>2</sub> " 0.1 ÷ 0.8 MPa / 14.5 ÷ 116 psi
Connections to liquid detergents:	8xø8 + 3xø12
Max. static load (with textile and water)	2.6 kN (A)
Max. dynamic load (intermittent vibrations)	2.2 ± 0.5 kN
Frequency of dynamic load	17.9 Hz

Part No. 1-16-58

	FX105	Date:	08/2011	No.	01–302–2
		Author:	RJ	Index/date	A/09.2013
		WASHER EXTRACTOR			