

TECHNICAL SPECIFICATION

Capacity:	1:10 - 24 kg
<u> </u>	max. 1:9 — 27 kg
Inner drum dimensions:	, , , , , , , , , , , , , , , , , , ,
diameter	750 mm / 29.5"
Drum volume:	240 dm3 / 52.8 gal
Drum revolutions:	
wash	42 rpm
high extraction	980 rpm
G-faktor:	402
Machine dimensions (max.):	
width	970 mm / 38.2"
depth	1105 mm / 43.5"
height	1435 mm /56.5"
Weight:	·
netto	430 kg / 948 lbs
brutto	450 kg / 992 lbs
Machine electrical execution:	E: 3x380-415V+N 50Hz
	S: 1x200-240V 50Hz (A)
Rated motor power:	3 kW
Rated heating power input:	18 kW
Rated input power of the machine:	E: 20 kW
	S: 3.1 kW (A)
Power supply protection — with el.heating	18kW/3AC 400V/40A
- without heating	1AC 20A
Conductors section (E / S)	5x6 mm ² Cu / 3x2.5 mm ² Cu
CONNECTIONS:	3x0 111111 Gu / 3x2.3 111111 Gu
recomended water pressure	0.3 ÷ 0.5 MPa
'	
water connection standard / option	2x ¾" / 3x ¾"
inlet of re-used water	ø19 mm
drain connection	ø76 mm / 3"
flow volume through drain valve	210 I/min
steam inlet	<i>7</i> 2"
steam pressure	0.1÷0.8 MPa
Connections to liquid detergents	8xø8 + 3xø12
Max. static load	5.3 kN (A)
(with textile and water)	5.5 NI
Max. dynamic load	4.6 ± 1.1 kN
(intermittent vibrations)	10.7.11
Frequency of dynamic load	16.3 Hz

Part No. 1-16-61

